

EC6900770



**BOARD FOR CONSTRUCTION SITE
ASC 5 SOCKETS IOSBF - PLUG**

Industrial > Cuadros de distribución > Cuadros de distribución
> Serie acs - sistema de paneles 700 > Serie acs - sistema de
paneles 700 > 5 tomas horizontales con bloqueo -
alimentación con clavija



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals

IP65

GWT
650°



RoHS II



MADE
IN
ITALY

Estándares

EN 61439-1 EN 61439-4

Etim

GROUP EG000023 - Distribution boards


CLASS EC000484 - Energy distributor for construction site

Rated current	32 etim.un.eu570459.abb	Leakage current type	Other	Degree of protection (IP)	IP65
Width	677 etim.un.eu570448.abb	Height	658 etim.un.eu570448.abb	Depth	288 etim.un.eu570448.abb
Model	Distributor cabinet	Housing material	Plastic	Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Number of miniature circuit breakers (MCB)	3	Rated voltage	400 V
Connected load	21 kW	Number of CEE socket outlets (IEC 60309) 16 A / 24 V / 2P (L, N)	0	Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 3P (L, N, PE)	2
Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 5P (1, 2, 3, N, PE)	0	Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 4P (1, 2, 3, PE)	2	Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 5P (1, 2, 3, N, PE)	0
Number of CEE socket outlets (IEC 60309) 32 A / 230 V / 4P (1, 2, 3, PE)	0	Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 4P (1, 2, 3, PE)	1	Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 5P (1, 2, 3, N, PE)	0
Number of CEE socket outlets (IEC 60309) 63 A / 230 V / 4P (1, 2, 3, PE)	0	Number of CEE socket outlets (IEC 60309) 63 A / 400 V / 5P (1, 2, 3, N, PE)	0	Number of CEE socket outlets (IEC 60309) 125 A / 230 V / 4P (1, 2, 3, PE)	0
Number of CEE socket outlets (IEC 60309) 125A / 400 V / 5P (1, 2, 3, N, PE)	0	Number of meter panels	0	Main switch	Other
Main switch rated current	32 etim.un.eu570459.abb	Number of poles main switch	4	Number of earth leakage switches 10 mA	0
Number of earth leakage switches 30 mA	1	Number of earth leakage switches 100 mA	0	Number of earth leakage switches 300 mA	0
Emergency stop button	Yes	Suitable according to IEC/EN 61439-4	Yes		

Technical Characteristics

Enchufes 32A 2P+E	-	protección de salida mt 16A	2x2P - 1x3P	protección de salida mt 32A	-
Enchufe 3P+N+E	32A				

Documentation available for download



Barcode



8056351662611

Unit

1 NR

26 [kg]