

EC6902101



ASSEMBLED DISTR. BOARD ASC TYPE 2 VERT. SOCKETS IP44 1X2P+E -1XITAL.

Industrial > Cuadros de distribución > Cuadros de distribución
> Asc - sistema de tableros > combinación de tomas de
corriente tipo cee (iec 60309) > 2x16a bases verticales



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals



Estándares

EN 61439-1 EN 61439-4

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)


Power loss	9 W	Leakage current type	AC	Degree of protection (IP)	IP44
Colour	Grey	Width	105 mm	Height	337 mm
Depth	95 mm	Housing material	Plastic	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Number of socket outlets with protective contact CEE 7/3 (type F)	1
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	CEE 16 A	Cable length	4 m
Protection	Overcurrent switch	Number of socket outlets Danish standard (earthing pin, type K)	0	CEE socket outlet 16 A	1x16A3p230V
CEE socket outlet 32 A	None	CEE socket outlet 63 A	None	CEE socket outlet 125 A	None
Other fixtures and/or empty locations	0	Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)	Number of miniature circuit breakers (MCB)	1
Power supply/connection possibility	Feeder cable with plug	Number of poles mains connection	3	Diameter cable entry	M25
Handling	Portable				

Technical Characteristics

Dispositivo diferencial	1 x2P 16A - 30mA	Dispositivo de protección de MT	combinato	Potencia máxima que se puede entregar	3.6 kW
Zócalos 2P+E	1	Zócalos 3P+N+E	-	Enchufes 3P+E	-
Schuko/encajes bivalentes	1				

Documentation available for download

Electical diagram



6902101.pdf

Barcode



8032793875079

Unit

1 NR

0.505x0.275x0.155 [m]

2.6 [kg]