

EC6902444



**ASS. DIS. BOARD ASC TYPE 2
SOCKETS IP44 1X2P+E 16 - 1X3P+E 32**

Industrial > Cuadros de distribución > Cuadros de distribución
> Asc - sistema de tableros > combinación de tomas de corriente tipo cee (iec 60309) > 2x16-32a bases horizontales con enclavamiento

Technical Symbols/Marks/Approvals



Estándares

EN 61439-1 EN 61439-4

Etim

**GROUP EG000014 - Industrial sockets/plug applications
CLASS EC000379 - CEE socket outlet combination (IEC 60309)**


| | | | | | |
|--|------------------------|--|--|--|-------------|
| Power loss | 24 W | Leakage current type | AC | Degree of protection (IP) | IP44 |
| Colour | Grey | Width | 360 mm | Height | 320 mm |
| Depth | 135 mm | Housing material | Plastic | Contact material | CuZn |
| Surface coating contacts | Untreated | Military model | No | Number of socket outlets with protective contact CEE 7/3 (type F) | 0 |
| Number of socket outlets Swiss standard type 13 | 0 | Number of socket outlets Swiss standard type 15 | 0 | Number of socket outlets Swiss standard type 23 | 0 |
| Number of socket outlets Swiss standard type 25 | 0 | Type of mains connection | CEE 32 A | Cable length | 4 m |
| Protection | Overcurrent switch | Number of socket outlets Danish standard (earthing pin, type K) | 0 | CEE socket outlet 16 A | 1x16A3p230V |
| CEE socket outlet 32 A | 1x32A xp xxxV | CEE socket outlet 63 A | None | CEE socket outlet 125 A | None |
| Other fixtures and/or empty locations | 0 | Earth leakage switch | Earth leakage switch with IFN 30 mA (standard) | Number of miniature circuit breakers (MCB) | 2 |
| Power supply/connection possibility | Feeder cable with plug | Number of poles mains connection | 5 | Diameter cable entry | M32 |
| Handling | Portable | | | | |

Technical Characteristics

| | | | | | |
|--------------------------------|------------------------------------|--|---------|----------------------------------|-------|
| Dispositivo diferencial | 1x2P 16A + 1x3P 32A DIFF. Puro 40A | Potencia máxima que se puede entregar | 21.0 kW | Zócalos 2P+E | 1x16A |
| Zócalos 3P+N+E | - | Enchufes 3P+E | 1x32A | Schuko/encajes bivalentes | - |

Documentation available for download

Electical diagram



6902444-2454.pdf

Barcode



8032793871767

Unit

1 NR

5.1 [kg]