



EC6902445



**ASS. DIS. BOARD ASC TYPE 2
SOCKETS IP44 1X2P+E 16 - 1X3P+N+E
32**

Industrial > Cuadros de distribución > Cuadros de distribución
> Asc - sistema de tableros > combinación de tomas de
corriente tipo cee (iec 60309) > 2x16-32a bases horizontales
con enclavamiento

Technical Symbols/Marks/Approvals



Estándares

EN 61439-1 EN 61439-4

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)

Power loss	24 W	Leakage current type	AC	Degree of protection (IP)	IP44
Colour	Grey	Width	360 mm	Height	320 mm
Depth	135 mm	Housing material	Plastic	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	CEE 32 A	Cable length	4 m
Protection	Overcurrent switch	Number of socket outlets Danish standard (earthing pin, type K)	0	CEE socket outlet 16 A	1x16A3p230V
CEE socket outlet 32 A	1x32A5p400V	CEE socket outlet 63 A	None	CEE socket outlet 125 A	None
Other fixtures and/or empty locations	0	Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)	Number of miniature circuit breakers (MCB)	2
Power supply/connection possibility	Feeder cable with plug	Number of poles mains connection	5	Diameter cable entry	M32
Handling	Portable				

Technical Characteristics

Dispositivo differenziale	1x2P 16A + 1x4P 32A DIFF. Puro 40A	Potencia máxima que se puede entregar	21.0 kW	Zócalos 2P+E	1x16A
Zócalos 3P+N+E	1x32A	Enchufes 3P+E	-	Schuko/encajes bivalentes	-

Documentation available for download

Electical diagram



6902445-2455.pdf

Barcode



8032793871774

Unit

1 NR

5.1 [kg]