



**EC6904542**

**ASS. DIS. BOARD DBO TYPE 2  
SOCKETS IP44 2X3P+N+E**



Industrial > Cuadros de distribución > Cuadros de distribución  
> Serie dbo - sistema de placas > combinación de tomas de  
corriente tipo cee (iec 60309) > 2x16a bases verticales  
entrelazados - con portafusibles

**Technical Symbols/Marks/Approvals**



**Estándares**

EN 61439-1 EN 61439-3

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC000379 - CEE socket outlet combination (IEC 60309)**

|                                                                        |           |                                                        |             |                                                                          |                              |
|------------------------------------------------------------------------|-----------|--------------------------------------------------------|-------------|--------------------------------------------------------------------------|------------------------------|
| <b>Power loss</b>                                                      | 24 W      | <b>Leakage current type</b>                            | Other       | <b>Degree of protection (IP)</b>                                         | IP44                         |
| <b>Colour</b>                                                          | Grey      | <b>Width</b>                                           | 320 mm      | <b>Height</b>                                                            | 510 mm                       |
| <b>Depth</b>                                                           | 135 mm    | <b>Housing material</b>                                | Plastic     | <b>Contact material</b>                                                  | CuZn                         |
| <b>Surface coating contacts</b>                                        | Untreated | <b>Military model</b>                                  | No          | <b>Number of socket outlets with protective contact CEE 7/3 (type F)</b> | 0                            |
| <b>Number of socket outlets Swiss standard type 13</b>                 | 0         | <b>Number of socket outlets Swiss standard type 15</b> | 0           | <b>Number of socket outlets Swiss standard type 23</b>                   | 0                            |
| <b>Number of socket outlets Swiss standard type 25</b>                 | 0         | <b>Type of mains connection</b>                        | Other       | <b>Protection</b>                                                        | Overcurrent switch/D0-system |
| <b>Number of socket outlets Danish standard (earthing pin, type K)</b> | 0         | <b>CEE socket outlet 16 A</b>                          | 2x16A5p400V | <b>CEE socket outlet 32 A</b>                                            | None                         |
| <b>CEE socket outlet 63 A</b>                                          | None      | <b>CEE socket outlet 125 A</b>                         | None        | <b>Other fixtures and/or empty locations</b>                             | 0                            |
| <b>Earth leakage switch</b>                                            | None      | <b>Number of miniature circuit breakers (MCB)</b>      | 1           | <b>Power supply/connection possibility</b>                               | 1 cable (branch line)        |
| <b>Number of poles mains connection</b>                                | 4         | <b>Diameter cable entry</b>                            | M32         | <b>Handling</b>                                                          | Wall mounting                |

## Technical Characteristics

|                                 |          |                                       |         |              |   |
|---------------------------------|----------|---------------------------------------|---------|--------------|---|
| Dispositivo de protección de MT | 1x4P 16A | Potencia máxima que se puede entregar | 10.5 kW | Zócalos 2P+E | - |
| Zócalos 3P+N+E                  | 2x16A    | Enchufes 3P+E                         | -       |              |   |

## Documentation available for download

### Electical diagram



6904542-4562.pdf

## Barcode



8033954870995

### Unit

1 NR

4 [kg]