



EC6904549



**ASS. DIS. BOARD DBO TYPE 2
SOCKETS IP44 1X2P+E 16 -1X3P+E 32**

Industrial > Cuadros de distribución > Cuadros de distribución
> Serie dbo - sistema de placas > combinación de tomas de
corriente tipo cee (iec 60309) > 2x16-32a bases verticales con
enclavamiento - con portafusibles

Technical Symbols/Marks/Approvals



Estándares

EN 61439-1 EN 61439-3

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)

Power loss	24 W	Leakage current type	Other	Degree of protection (IP)	IP44
Colour	Grey	Width	320 mm	Height	510 mm
Depth	135 mm	Housing material	Plastic	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	Other	Protection	Overcurrent switch/D0-system
Number of socket outlets Danish standard (earthing pin, type K)	0	CEE socket outlet 16 A	1x16A3p230V	CEE socket outlet 32 A	1x32A xp xxxV
CEE socket outlet 63 A	None	CEE socket outlet 125 A	None	Other fixtures and/or empty locations	0
Earth leakage switch	None	Number of miniature circuit breakers (MCB)	1	Power supply/connection possibility	1 cable (branch line)
Number of poles mains connection	4	Diameter cable entry	M32	Handling	Wall mounting

Technical Characteristics

Dispositivo de protección de MT	1x4P 32A	Potencia máxima que se puede entregar	21.0 kW	Zócalos 2P+E	1x16A
Zócalos 3P+N+E	-	Enchufes 3P+E	1x32A		

Documentation available for download

Electical diagram



6904549-4569.pdf

Barcode



8033954871060

Unit

1 NR

4 [kg]