



EC6904620



**ASS. DIS. BOARD DBO TYPE 3
SOCKETS IP44 2X2P+E -1X3P+E 16**

Industrial > Cuadros de distribución > Cuadros de distribución
> Serie dbo - sistema de placas > Serie dbo - sistema de
placas > 3x16-32a bases verticales entrelazados - con
portafusibles

Technical Symbols/Marks/Approvals



Estándares

EN 61439-1 EN 61439-3

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)


Power loss	30 etim.un.eu570054.abb	Leakage current type	Other	Degree of protection (IP)	IP44
Colour	Grey	Width	400 etim.un.eu570448.abb	Height	525 etim.un.eu570448.abb
Depth	135 etim.un.eu570448.abb	Housing material	Plastic	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	Other	Protection	Overcurrent switch/D0-system
Number of socket outlets Danish standard (earthing pin, type K)	0	CEE socket outlet 16 A	3x16A xp xxxV	CEE socket outlet 32 A	None
CEE socket outlet 63 A	None	CEE socket outlet 125 A	None	Other fixtures and/or empty locations	0
Earth leakage switch	None	Number of miniature circuit breakers (MCB)	2	Power supply/connection possibility	1 cable (branch line)
Number of poles mains connection	4	Diameter cable entry	M32	Handling	Wall mounting

Technical Characteristics

Dispositivo de protección de MT	1x2P 16A + 1x3P 16A	Potencia máxima que se puede entregar	14.1 kW	Zócalos 2P+E	2x16A
Zócalos 3P+N+E	-	Enchufes 3P+E	1x16A		

Documentation available for download

Electical diagram



6904620-4630.pdf

Barcode



8032793871606

Unit

1 NR

4.5 [kg]