



EC6909641F

**WALL-MOUNT VERT. INTERLOCKED
SOCKET WITH FUSE HOLDER IP44
380V 3P+E 32A**



Industrial > Tomas y clavijas > Con bloqueo > Vertical - con portafusibles > enchufe cee desconectable, protegido por fusible (iec 60309) > Ip44

Technical Symbols/Marks/Approvals

IP44	IK08	HF	CE	RoHS II	ME	MADE IN ITALY
------	------	----	----	---------	----	---------------

Estándares

EN 60309-1 EN 60309-2 EN 60309-4

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	4	Degree of protection (IP)	IP44	Model	Base unit and cover
Housing material	Plastic	IEC-amperage	32 A	Voltage according to EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h	Identification colour	Red	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Protection	Cylindrical fuse
Switch	Mechanical locking	With earth leakage switch	No	Empty locations on mounting rail	No

Documentation available for download



Barcode



8033954872203

Unit

1 NR

0.295x0.12x0.15 [m]

1.317 [kg]



8059307216975

Cardboard

10 NR

0.605x0.4x0.35 [m]

13.17 [kg]