



**EC690964F**

**PANEL-MOUNT VERT. INTERLOCKED  
SOCKET WITH FUSE HOLDER IP44  
380V 3P+E 32A**



Industrial > Bases y clavijas > Con bloqueo > Vertical - con portafusibles > enchufe cee desconectable (iec 60309) > Ip44

**Technical Symbols/Marks/Approvals**



**Estándares**

EN 60309-1 EN 60309-2 EN 60309-4

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)**

|                                 |                    |                                  |      |                                         |                      |
|---------------------------------|--------------------|----------------------------------|------|-----------------------------------------|----------------------|
| <b>Number of poles</b>          | 4                  | <b>Degree of protection (IP)</b> | IP44 | <b>Model</b>                            | Top cover            |
| <b>Housing material</b>         | Plastic            | <b>IEC-amperage</b>              | 32 A | <b>Voltage according to EN 60309-2</b>  | 400 V (50+60 Hz) red |
| <b>Clock hour position</b>      | 6 h                | <b>Identification colour</b>     | Red  | <b>Contact material</b>                 | CuZn                 |
| <b>Surface coating contacts</b> | Untreated          | <b>Military model</b>            | No   | <b>Protection</b>                       | Cylindrical fuse     |
| <b>Switch</b>                   | Mechanical locking | <b>With earth leakage switch</b> | No   | <b>Empty locations on mounting rail</b> | No                   |

**Documentation available for download**



## Barcode



8033954872029

**Unit**

1 NR

0.295x0.12x0.15 [m]

1.073 [kg]



8059307216982

**Cardboard**

10 NR

0.605x0.4x0.35 [m]

10.73 [kg]