

EC69098



PANEL-MOUNT HORIZ. INTERLOCKED SOCKET IP44 380V 3P+N+E 32A

Industrial > Tomas y clavijas > Con bloqueo > Horizontal - sin
portafusibles > enchufe cee desconectable, protegido por
fusible (iec 60309) > Ip44



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals

IP44	IK08	HF	CE	RoHS II			MADE IN ITALY
------	------	----	----	---------	--	--	---------------------

Estándares

EN 60309-1 EN 60309-2 EN 60309-4

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	5	Degree of protection (IP)	IP44	Model	Top cover
Housing material	Plastic	IEC-amperage	32 A	Voltage according to EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h	Identification colour	Red	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Protection	None
Switch	Mechanical locking	With earth leakage switch	No	Empty locations on mounting rail	No

Documentation available for download



Certification

IMQ_CA02.05700_
2025_32A_IOSBF.p
df

Barcode



8032636764386

Unit

1 NR

0.17x0.12x0.12 [m]

0.5 [kg]



8059307217088

Cardboard

24 NR

0.6x0.415x0.44 [m]

12 [kg]