

EC6910845



**D. BOARD FOR CONSTR.SITE
2XITAL.-2X2P16-1X3P16A-1X3P+N16A-
1X3P32A-1X3P+N32A**



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Industrial > Cuadros de distribución > Cuadros de distribución
> Serie asc - sistema de paneles 800 > Cuadro eléctrico para
obra > 6 bases horizontales con bloqueo- alimentación con
bornera

Technical Symbols/Marks/Approvals

IP65

GWT
650°



CE

RoHS II



MADE
IN
ITALY

Estándares

EN 61439-1 EN 61439-4

Etim

GROUP EG000023 - Distribution boards


CLASS EC000484 - Energy distributor for construction site

Rated current	32 A	Leakage current type	Other	Degree of protection (IP)	IP65
Width	870 mm	Height	720 mm	Depth	375 mm
Model	Distributor cabinet	Housing material	Plastic	Number of socket outlets with protective contact CEE 7/3 (type F)	2
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Number of miniature circuit breakers (MCB)	3	Rated voltage	400 V
Connected load	21	Number of CEE socket outlets (IEC 60309) 16 A / 24 V / 2P (L, N)	0	Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 3P (L, N, PE)	2
Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 5P (1, 2, 3, N, PE)	0	Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 4P (1, 2, 3, PE)	1	Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 5P (1, 2, 3, N, PE)	1
Number of CEE socket outlets (IEC 60309) 32 A / 230 V / 4P (1, 2, 3, PE)	0	Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 4P (1, 2, 3, PE)	1	Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 5P (1, 2, 3, N, PE)	1
Number of CEE socket outlets (IEC 60309) 63 A / 230 V / 4P (1, 2, 3, PE)	0	Number of CEE socket outlets (IEC 60309) 63 A / 400 V / 5P (1, 2, 3, N, PE)	0	Number of CEE socket outlets (IEC 60309) 125 A / 230 V / 4P (1, 2, 3, PE)	0
Number of CEE socket outlets (IEC 60309) 125A / 400 V / 5P (1, 2, 3, N, PE)	0	Number of meter panels	0	Main switch	Other
Main switch rated current	32 A	Number of poles main switch	4	Number of earth leakage switches 10 mA	0
Number of earth leakage switches 30 mA	1	Number of earth leakage switches 100 mA	0	Number of earth leakage switches 300 mA	0
Emergency stop button	Sí	Suitable according to IEC/EN 61439-4	Sí		

Technical Characteristics

Dispositivo diferencial	combinato	Prese_16A_2P+T	2	Prese_32A_2P+T	-
Prese_16A_3P+N+T	1	Prese_16A_3P+T	1	Schuko/encajes bivalentes	2
protección de salida mt 16A	1x2P - 1x4P	protección de salida mt 32A	combinato	shuko bivalente 16A 2P+E	2
prese_32A_3P+T	1	Prese_32A_3P+N+T	1	Prese_63A_3P+N+T	-
Prese_63A_3P+T	-				

Documentation available for download



Instruction booklet

GUIDA DI
RIFERIMENTO
QUADRI DA
CANTIERE TIPO
69008.pdf



Electrical diagram

6910845.pdf

Barcode



8053676572724

Unit

1 NR

1.025x0.395x0.74 [m]

34 [kg]