

## EC699P17

### INDUSTRIAL EXTENSION IP44 3P+E 30 m



IMMAGINE  
RAPPRESENTATIVA



REPRESENTATIVE  
IMAGE

Industrial > Enrolladores y cables de extensión > Enrolladores y cables de extensión > Extensiones industriales > Cable de alimentación > 16 a - ip44

#### Technical Symbols/Marks/Approvals

IP44



RoHS II



MADE  
IN  
ITALY

#### Estándares

EN 60309-1 EN 60309-2

## Etim

GROUP EG000053 - Batteries, chargers and power cords

CLASS EC001576 - Power cord

|                                                                      |                     |                                                   |                          |                                                            |                      |
|----------------------------------------------------------------------|---------------------|---------------------------------------------------|--------------------------|------------------------------------------------------------|----------------------|
| Degree of protection (IP)                                            | IP44                | Length                                            | 30 m                     | Material outer sheath                                      | Rubber               |
| Colour outer sheath                                                  | Black               | Reaction-to-fire according to EN 13501-6: Class   | Eca                      | Reaction-to-fire according to EN 13501-6: Smoke production | None                 |
| Reaction-to-fire according to EN 13501-6: Flaming droplets/particles | None                | Reaction-to-fire according to EN 13501-6: Acidity | None                     | Outer diameter approximate                                 | 15.5 mm              |
| Nominal voltage                                                      | 380-415 V           | Frequency                                         | 50-60 Hz                 | Number of cores                                            | 4                    |
| Nominal cross section conductor                                      | 2.5 mm <sup>2</sup> | Nominal current                                   | 16 A                     | Temperature resistance                                     | -25-60 °C            |
| With protective conductor                                            | Sí                  | Oil resistant according to EN IEC 60811-404       | Sí                       | Connection 1                                               | CEE plug (IEC 60309) |
| Cable entry connection 1                                             | Straight            | Connection 2                                      | CEE coupling (IEC 60309) | Cable entry connection 2                                   | Straight             |
| System-oriented connector system                                     | No                  | Spiralized cable                                  | No                       | With cord switch                                           | No                   |

## Technical Characteristics

Cable de alimentación  
desenrollado 11.0 kW

## Barcode



8033954873422

**Unit**

1 NR

0.505x0.275x0.155 [m]

6.45 [kg]