

EC699P27

INDUSTRIAL EXTENSION IP67 3P+E 30 m



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Industrial > Enrolladores y cables de extensión > Enrolladores y cables de extensión > Extensiones industriales > Cable de alimentación > 16 a - ip67

Technical Symbols/Marks/Approvals

IP67



RoHS II



MADE
IN
ITALY

Estándares

EN 60309-1 EN 60309-2

Etim

GROUP EG000053 - Batteries, chargers and power cords

CLASS EC001576 - Power cord

Degree of protection (IP)	IP67	Length	30 m	Material outer sheath	Rubber
Colour outer sheath	Black	Reaction-to-fire according to EN 13501-6: Class	Eca	Reaction-to-fire according to EN 13501-6: Smoke production	None
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	None	Reaction-to-fire according to EN 13501-6: Acidity	None	Outer diameter approximate	15.5 mm
Nominal voltage	380-415 V	Frequency	50-60 Hz	Number of cores	4
Nominal cross section conductor	2.5 mm ²	Nominal current	16 A	Temperature resistance	-25-60 °C
With protective conductor	Sí	Oil resistant according to EN IEC 60811-404	Sí	Connection 1	CEE plug (IEC 60309)
Cable entry connection 1	Straight	Connection 2	CEE coupling (IEC 60309)	Cable entry connection 2	Straight
System-oriented connector system	No	Spiralized cable	No	With cord switch	No

Technical Characteristics

Cable de alimentación
desenrollado 11.0 kW

Barcode



8033954873514

Unit

1 NR

0.505x0.275x0.155 [m]

6.45 [kg]