

EC16001

DOUBLE SIDED MODULAR BOXES 2+2 DEVICES WITH 60 mm CENTRE HOLE - GREY



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Goulottes > Gestion des câbles au sol > Systèmes de distribution au sol > Caissons de sol utilitaires > Coffret de sol posé en saillie, vide > Caissons de sol

Symboles/marques/approbations techniques

IK07	IP54	GWT 650°	CE	RoHS II	MADE IN ITALY
------	------	-------------	----	---------	---------------------

Normes

EN 50085-1 EN 50085-2-4

Description

Double-sided tower made of shock-resistant technopolymer. Designed for 4+4 fixtures with 108.5 mm spacing or for 2+2 fixtures with 60 mm spacing. End cap included for single-sided use. Designed for the entry of 75x17 and 50x12 mm floor trunking. Can be installed on poured or raised floors.

Etim

GROUP EG000005 - Systèmes d'installation électrique enterrés

CLASS EC000121 - Coffret de sol posé en saillie, vide


Matériau	Autre	Traitement de surface	Autre	Couleur	Gris
Largeur	150 mm	Hauteur	149 mm	Modèle	Horizontal
Longueur	226 mm	Numéro RAL	7030	Nombre d'appareils encastrables	8
Nombre d'appareils encastrables, face arrière	4	Nombre d'appareils encastrables, face avant	4	Adapté à un matériau de commutation standard	Oui
Adapté à un nettoyage humide	Oui				

Caractéristiques techniques

Qualité IP	54	empattement	108.5 mm
------------	----	-------------	----------

Documentation disponible en téléchargement

Instruction booklet



Istruzioni_SERIE_1
60_0423.pdf

Code à barres



8033576771762

Unit

1 NR

0.16x0.22x0.155 [m]

0.791 [kg]



8059307212441

Cardboard

10 NR

0.4x0.605x0.35 [m]

7.91 [kg]