

## EC16001H

### HORIZ. EXPANSIONS 2+2 DEVICES WITH 60 mm CENTRE HOLE - GREY



IMMAGINE  
RAPPRESENTATIVA



REPRESENTATIVE  
IMAGE

Goulottes > Gestion des câbles au sol > Systèmes de distribution au sol > Support de sol appareillage > Coffret de sol posé en saillie, vide > Kits d'extension

#### Symboles/marques/approbations techniques

IK07

IP54

GWT  
650°



RoHS II

MADE  
IN  
ITALY

#### Normes

EN 50085-1 EN 50085-2-4

## Description

Horizontal expansion for double-sided tower made of shock-resistant technopolymer. Designed for 4+4 fixtures with 108.5 mm spacing or for 2+2 fixtures with 60 mm spacing. End cap included for single-sided use. Designed for the entry of 75x17 and 50x12 mm floor trunking. Can be installed on poured or raised floors.

## Etim

GROUP EG000005 - Systèmes d'installation électrique enterrés

CLASS EC000121 - Coffret de sol posé en saillie, vide


|                                               |        |                                             |        |                                              |            |
|-----------------------------------------------|--------|---------------------------------------------|--------|----------------------------------------------|------------|
| Matériau                                      | Autre  | Traitement de surface                       | Autre  | Couleur                                      | Gris       |
| Largeur                                       | 150 mm | Hauteur                                     | 149 mm | Modèle                                       | Horizontal |
| Longueur                                      | 176 mm | Numéro RAL                                  | 7030   | Nombre d'appareils encastrables              | 8          |
| Nombre d'appareils encastrables, face arrière | 4      | Nombre d'appareils encastrables, face avant | 4      | Adapté à un matériau de commutation standard | Oui        |
| Adapté à un nettoyage humide                  | Oui    |                                             |        |                                              |            |

## Caractéristiques techniques

|            |    |             |          |
|------------|----|-------------|----------|
| Qualité IP | 54 | empattement | 108.5 mm |
|------------|----|-------------|----------|

## Documentation disponible en téléchargement

### Instruction booklet



Istruzioni\_SERIE\_1  
60\_0423.pdf

## Code à barres



8033576771786

### Unit

1 NR

0.2x0.154x0.145 [m]

0.671 [kg]



8059307212458

### Cardboard

10 NR

0.605x0.4x0.35 [m]

6.71 [kg]