




FLEXIBLE SLOTTED TRUNKING SCREW FIXING 12,5X12,5X500

Goulottes > SystÈmes de tableaux de distribution > SystÈmes de cÂblage > Goulottes de cablage flexibles > Goulotte de câblage > Trous de fixation perforÉs



Symboles/marques/approbations techniques

UL94	CC	RoHS II	MADE IN
V2	6	HOHS II	ITALY

Normes

EN 50085-1 EN 50085-2-3 UL 1565

Description

Flexible wiring duct made of self-extinguishing UL94-V2 polypropylene technopolymer. Pre-drilled bottom for installation with fixing screws.

Etim

GROUP EG000007 - Goulottes de câblage CLASS EC000012 - Goulotte de câblage

Matériau	Polypropylène	Sans halogène	No	Couleur	Gris
Type de fixation	Perforation du fond	Largeur	12.5 mm	Hauteur	12.5 mm
Longueur	500 mm	Distance entre les fentes	7.5 mm	Largeur de fente	7.5 mm
Finition de paroi latérale	Rainuré	Auto-extinguible	Oui	Flexible	Oui
Section transversale utile	121 mm ²	Avec partie supérieure	Oui	Numéro RAL	7030





Code à barres



8050880881253

Cardboard

112 NR

1.4 [kg]