



EC23401

**FLEXIBLE SLOTTED TRUNKING
SCREW FIXING 12,5X12,5X500**



Goulettes > Systèmes de tableaux de distribution > Systèmes de câblage > Goulettes de câblage flexibles > Goulotte de câblage > Trous de fixation perforés

Symboles/marques/approbations techniques



Normes

EN 50085-1 EN 50085-2-3 UL 1565

Description

Flexible wiring duct made of self-extinguishing UL94-V2 polypropylene technopolymer. Pre-drilled bottom for installation with fixing screws.

Etim

GROUP EG000007 - Goulettes de câblage

CLASS EC000012 - Goulotte de câblage

| | | | | | |
|-----------------------------------|---------------------|----------------------------------|---------|-------------------------|---------|
| Matériau | Polypropylène | Sans halogène | No | Couleur | Gris |
| Type de fixation | Perforation du fond | Largeur | 12.5 mm | Hauteur | 12.5 mm |
| Longueur | 500 mm | Distance entre les fentes | 7.5 mm | Largeur de fente | 7.5 mm |
| Finition de paroi latérale | Rainuré | Auto-extinguible | Oui | Flexible | Oui |
| Section transversale utile | 121 mm ² | Avec partie supérieure | Oui | Numéro RAL | 7030 |

Code à barres



8050880881253

Cardboard

112 NR

1.4 [kg]