

EC90010060



**TRUNKING WITH COVER FOR AIR-
CONDITIONED INSTALLATION DIM.
100X60**



Goulottes > Climatisation > Goulottes et accessoires >
Goulottes > Goulotte d'installation

Symboles/marques/approbations techniques

IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

UL94
V0

GWT
960°

IP40



RoHS II

MADE
IN
ITALY

Description

Air conditioning duct made of self-extinguishing rigid PVC technopolymer. Pre-drilling of the bottom for fixing with screws and plugs. Designed for attaching cable ties. Wrap-around cover included.

Etim

GROUP EG000006 - Goulottes d'installation murales et de plafond

CLASS EC001938 - Goulotte d'installation

Classe de protection (IP)	IP40	Matériau	Plastique	Qualité du matériau	PVC
Sans halogène	No	Traitement antibactérien	No	Traitement de surface	Non traité
Couleur	Blanc	Résistance aux chocs	IK07	Largeur	100 mm
Profondeur	60 mm	Longueur	2 m	Section transversale utile	5120 mm²
Numéro RAL	9001	Type de montage des parties supérieures	Global	Film de protection	No
Température d'utilisation	-25-70 °C	Nombre de cloisons enfichables	0	Avec agrafe pour tenue de câble	No
Avec connecteur de conduit	No	Perforation de montage dans le sol	No	Nombre de parties supérieures	1
Largeur de la partie supérieure 1	100 mm	Symétrique	Oui	Parties supérieures fournies	Oui
Type rectangulaire	Oui	Finition du panneau arrière (intérieur)	Perforé		

Code à barres



8050880884803

Cardboard

16 MT

0.26x0.18x2.027 [m]

13.3008 [kg]