

EC9008060



TRUNKING WITH COVER FOR AIR-CONDITIONED INSTALLATION DIM. 80X60

Goulottes > Climatisation > SystÈmes de climatisation > Goulottes > Goulotte d'installation



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Symboles/marques/approbations techniques

UL94 V0	GWT 960°	IP40	CE	RoHS II	MADE IN ITALY
------------	-------------	------	----	---------	---------------------

Description

Air conditioning duct made of self-extinguishing rigid PVC technopolymer. Pre-drilling of the bottom for fixing with screws and plugs. Designed for attaching cable ties. Wrap-around cover included.

Etim

GROUP EG000006 - Goulottes d'installation murales et de plafond

CLASS EC001938 - Goulotte d'installation

Classe de protection (IP)	IP40	Matériau	Plastique	Qualité du matériau	PVC
Sans halogène	No	Traitement antibactérien	No	Traitement de surface	Non traité
Couleur	Blanc	Résistance aux chocs	IK07	Largeur	80 mm
Profondeur	60 mm	Longueur	2 m	Section transversale utile	3910 mm²
Numéro RAL	9001	Type de montage des parties supérieures	Global	Film de protection	No
Température d'utilisation	-25-70 °C	Nombre de cloisons enfichables	0	Avec agrafe pour tenue de câble	No
Avec connecteur de conduit	No	Perforation de montage dans le sol	No	Nombre de parties supérieures	1
Largeur de la partie supérieure 1	80 mm	Symétrique	Oui	Parties supérieures fournies	Oui
Type rectangulaire	Oui	Finition du panneau arrière (intérieur)	Perforé		

Code à barres



8050880884834

Cardboard

16 MT

0.248x0.143x2.03 [m]

12 [kg]